



Refrigerator cabinet to preserve  
pharmaceutical and biological materials.

## Blood Bank Refrigerator Small Size

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
BB 0021 NFP	+2°C ÷ +8°C	+4°C	120	45 x 64 x 140	Glass Door



**Alarm: HI Limit +8°C ; LOW Limit +2°C**

**Blood bags (450ml): max 63 (3 drw.)**

**Blood bags (250ml): max 81 (3 drw.)**

**Blood tubes : max 940 (4 shelves + bottom)**

**Colour:** Gray, White or any RAL colour

**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity

**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m<sup>3</sup>, thickness 80mm

**Refrigeration type:** Ventilated (NO-FROST)

**Defrosting:** Automatic with condensing water evaporation

**Electric power:** 1 / 210-240Volt / 50-60Hz

**Compressor:** nr.1 Hermetic Type - 400Watt

**Refrigerant gas:** R452a (R507a and R404a compatible)

**Door:** : No. 1 Glass Door

**Inner setting:** 3 Drawers

**Lighting:** NEON lamp active on opening door

**Electronic controller:** Hi Efficiency display, res. 0,1°C

**Castors and Wheels:** 4 Wheels + 2 adjustable feet

**ACCURACY:** 0.1°C

**Visual and acoustic alarm for:**

- High and low temperature
- Open door
- Devices failure
- Probes failures

**OPTIONAL:**

DTLSD3 - Data Logger Touch Screen 5"

SE / ESE /SEDL - Manual or Electronic Lock

UPS - Back-up Battery System

CHAUT - Self Closing Door

HELO - Hole for External Probe

LED - LED Lamp Inside

CS1 / CS2 - Sliding Movable S/Steel Drawers

SH1 / SH2 - Sliding Movable S/Steel Shelves

WI-FI/3G – On-line Monitoring and Remote Alarm

