



Refrigerator cabinet to preserve pharmaceutical and biological materials.

Blood Bank Refrigerator Small Size

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
BB LP460 NFP	+2°C ÷ +8°C	+4°C	100 Net	46 x 55 x 108	Glass Door



HI Limit +8°C ; LOW Limit +2°C ; SET: +4°C
BACK-UP Battery and DRY CONTACT

Blood bags (450ml): max 44 (3 drw.)

Blood bags (250ml): max 66 (3 drw.)

Blood tubes : approx. 240 (3 shelves + bottom)

Colour: Gray, White or any RAL colour

Structure: Internal and external Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY™ to assure a Bacteria-Static Activity

Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 70mm

Refrigeration type: Ventilated (NO-FROST)

Defrosting: Automatic with condensing water evaporation

Electric power: 1 / 210-240Volt / 50-60Hz

Compressor: No.1 Hermetic Type - 250Watt

Refrigerant gas: R452a (R404a and R507a Compatible)

Door: No. 1 Glass Door

Inner setting: 2 to max 3 Drawers/Shelves/Grids

Lighting: NEON lamp active on opening door (LED opt.)

Electronic controller: Hi Efficiency display, Accuracy 0.1°C

Castors and Wheels: 4 feet

Main Visual - Acoustic alarm for: -HI and LOW temperature

- Open door
- Devices failure
- Power failures

OPTIONAL:

DTLSD3 – Interactive Data Logger TFT 5"

ESEDL - Electronic Lock with Password

CHAUT - Self Closing Door with Stopper at 95°

HELO - Hole for External Probe

LED - LED Lamp Inside (standard with DTLSD3)

CS1 - Sliding Aluminum or S/S Drawers

SH1 - Sliding S/S Shelves

WI-FI or 3G – On-line Monitoring and Controlling, e-mails sending in case of warnings and errors

SMS – SMS system in case of error

