

no frost system  
Refrigerator cabinet to preserve pharmaceutical and biological materials.

# Plasma & Lab Deep Freezer

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
DFP 5030NFA	0°C ÷ -40°C	-35°C (adj.)	880	95 x 89 x 204	Hinged Solid Door



**DRY CONTACT – BACK-UP BATTERY (ups) – ACCURACY 0.1°**  
**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, Thick. 90mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** No 2 Hermetic Type – 2 x 900Watt – 1 HP each  
**Refrigerant gas:** R507A  
**Door:** : No 1 Solid Door  
**Inner setting:** 5/6 Adjustable Shelves/Grids  
**Lighting:** -----  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 wheels + 2 adjustable feet  
**Visual and acoustic alarm for:** - HI and LOW temperature  
 - Open door  
 - Devices failure  
 - Probes failures  
 - Compressor failure  
 - Condenser failure  
 - UPS failure

**OPTIONAL:**  
 DTLS-1T - Data Logger Touch Screen Velex 5" D3  
 SE / ESEDL - Manual or Electronic Lock  
 UPS - Back-up Battery System (Standard)  
 CHAUT - Self Closing Door  
 LED – Led light when door open  
 HELO - Hole for External Probe  
 CS2 - Sliding Movable S/Steel Drawers  
 SH2 - Sliding Movable S/Steel Shelves  
 SMS - SMS Alarm System  
 3G/WI-FI – Online connection for remote monitoring system

TWIN COOLING SYSTEM

Option: INTERACTIVE DIGITAL DATA LOGGER TOUCH SCREEN 5"

