



# Plasma & Lab Deep Freezer 2 Compartments

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	DIMENSIONS (WxDxH cm)	DOOR TYPE
DFP8000NFA	0°C ÷ -45°C	-35°C (adj.)	400+400	<b>External</b> 132 x 89 x 204 <b>Internal</b> 57x54x130 x2	Two Solid Door



## DRY CONTACT-BACK-UP BATTERY 24h-ACCURACY 0.1°

- Colour:** Grey, White or any RAL colour
- Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, Thick. 90mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 220-240Volt / 50-60Hz
- Compressor:** No 2 Hermetic Type – 2 x 900Watt – 1 HP each
- Refrigerant gas:** R452a (R404a and R507a compatible)
- Door:** : No 2 Solid Door
- Inner setting:** 5/6 Adjustable Shelves/Grids
- Lighting:** -----
- Electronic controller:** Hi Efficiency display, res. 0,1°C
- Castors and Wheels:** 4 wheels + 2 adjustable feet
- Visual and acoustic alarm for:**
  - High and Low temperature
  - Open door
  - Devices failure
  - Probes failures
  - Compressor failure
  - Condenser failure
  - UPS failure

## OPTIONAL:

- DTLSD3 – Interactive Data Logger Touch Screen LCD 5"
- SE / ESEDL - Manual or Electronic Lock
- CHAUT - Self Closing Door
- LED – Led light when door open
- HELO - Hole for External Probe
- CS1 - Sliding Movable S/Steel or Aluminum Drawers
- SH1 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- 3G/WI-FI – Online connection for remote monitoring system

2 TWIN COOLING SYSTEM ON BOARD



S/STEEL SLIDING SHELVES



SLIDING DRAWERS

