



Laboratory Refrigerator

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
0040 NFP	+2°C ÷ +10°C	+4°C	210	67 x 64 x 140	Solid Door



ACCURACY: 0.1°C - MICRO-PROCESSOR CONTROLLED
Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 80mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage (+/- 20 Volts)
Compressor: No 1 Hermetic Type - 450Watt ,1/3 HP
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : No 1 Glass Door
Inner setting: 3 / 4 Shelves/Grids
Lighting: NEON lamp active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

- DTLSD3 - Data Logger Touch Screen 5"
- TC - Twin Compressor
- SE / EESDL - Manual or Electronic Lock with Password
- UPS - Back-up Battery System
- CHAUT - Self Closing Door
- HELO - Hole for External Probe
- LED - LED Lamp Inside
- CS1 / CS2 - Sliding Movable S/Steel Drawers
- SH1 / SH2 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI/3G-Connection to the Network for remote control online

