



Laboratory Freezer 2 Indep. Compartments

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LT.)	EXTERNAL DIMENSIONS (W x D x H cm)	DOORS
10000NFN	0°÷-35°C/0°÷-35°C	-30°C/-30°C	470+470	150 x 64 x 204	2 Solid Doors



MICRO-PROCESSOR CONTROLLED-UPS (Back-up Battery) 24hr DRY CONTACT

Colour: Grey, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick.70mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 220-240Volt / 50-60Hz
Compressor: No 2 Hermetic Type- 500+500 Watts - ½+½ HP
Refrigerant gas: R452a (compatible to R404a and R507a)
Door: : No 2 Solid Doors
Inner setting: 10/12/14/16 Shelves/Grids/Drawers/Sliding Shelves
Lighting: NEON or LED lamp active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 6 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW Temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLSD3 (2T) – Interactive Data Logger Touch Screen 5" (TFT)
 TC - Twin Compressor
 SE / ESEDL - Manual or Electronic Lock
 CHAUT - Self Closing Door
 HLO - Hole for External Probe
 LED - LED Lamp Inside
 CS2 - Sliding Movable Aluminum Drawers
 SH2 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm System
 WI-FI/3G-On-line connection, e-mail warning, real time control
 S – Special Temperature -35°C
 RS385 / ETH – Exit RS485 or Ethernet for remote connection

