



Laboratory Freezer , 2 Compartments

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOORS
10000NFN	0°C ÷ -25°C	-20°C/-20°C	470+470	150 x 64 x 204	2 Solid Doors



MICRO-PROCESSOR CONTROLLED – UPS (Back-up Battery) DRY CONTACT

Colour: Grey, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thic.80mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 220-240Volt / 50-60Hz
Compressor: No 1 Hermetic Type– 1000 Watts – 1 ¼ HP
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : No 2 Solid Doors
Inner setting: 10/12 Shelves/Grids
Lighting: NEON lamp active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 6 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLSD3 (1T) - Data Logger Touch Screen 5" Vexel
 TC - Twin Compressor
 SE / ESEDL - Manual or Electronic Lock
 CHAUT - Self Closing Door
 HELO - Hole for External Probe
 LED - LED Lamp Inside
 CS2 - Sliding Movable Aluminum Drawers
 SH2 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm System
 WI-FI/3G-On-line connection, e-mail warning, real time control
 S – Special Temperature -35°C
 RS385 / ETH – Exit RS485 or Ethernet for remote connection

