



Laboratory Vaccine Freezer Storage

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
LB 2000NFN	+0°C ÷ -35°C	-30°C(Adj.)	250	45 x 64 x 203	Hinged Solid Door



MICRO PROCESSOR CONTROLLED-BACK-UP BATTERY 12v/48h

Colour: Gray, White or any RAL colour
Structure: Internal and external Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY® to assure a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 70mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz, 10 Amp
Electrical characteristics: Shortage Protection, Power Stabilizer with Linear Voltage Regulation for not constant voltage(+/- 25V)
Compressor: nr.1 Hermetic Type - 600Watt
Refrigerant gas: R452a (R404a and R507a compatible)
Door: No. 1 Hinged Solid Door
Inner setting: 5 to 11 Shelves/Grids
Lighting: LED lamp active on opening door
Electronic controller: FLEX PHARMA or DTLSD3, WI-FI Connection, Data Download, Accuracy. 0,1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Standard Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLS(1T) – Interactive Data Logger D3, TFT 5", RGB Colors
 IR33R – IR33U – Digital Temperature Controller LED Display
 SE / ESE /SEDL - Manual or Electronic Lock
 CHAUT - Self Closing Door with stopper at 95°
 HLO - Hole for External Probe
 CS1 - Sliding Movable S/Steel Drawers
 SH1 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm System
 3G or WI-FI - Connection online for Alarms Sending, Real Time Monitoring Functions, Weekly auto-sending report
 HC - Humidity Controller
 TR – Tropical Cooling System for temp. till 42°C and RH <90%

OPTION INTERACTIVE DIGITAL DATA LOGGER 5"

