


Laboratory Freezer -35 °C



MODEL	TEMPERATURE SET RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
LB 7100 NFN	0°C ÷ -35°C	820	132 x 64 x 204	Two Solid Doors



DRY CONTACT – BACKUP BATTERY – ACCURACY 0.1°C

- Colour:** Grey, White or any RAL colour
- Structure:** Internal and external Steel Laminated Plate FINGER PRINT PROOF TECHNOLOGY to assure a Bacteriastatic Activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thic. 70mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 220-240Volt / 50-60Hz
- Compressor:** No.1 Hermetic Type– 900 Watts – 1 HP
- Refrigerant gas:** R452a (Compatible with R507a and R404a)
- Door:** : No 2 Solid Doors
- Inner setting:** 10/12 Shelves/Grids
- Lighting:** NEON lamp active on opening door
- Electronic controller:** Hi Efficiency display, res. 0,1°C
- Castors and Wheels:** 4 wheels + 2 adjustable feet

- Main Visual and acoustic alarm for:
- High and Low temperature
 - Open door
 - Devices failure
 - Probes failures

MAIN OPTIONS:

- DTLSD3(1T) - Interactive Digital Data Logger TFT 5"
- TC - Twin Compressor with Backup function if faulty
- SE / ESDL - Manual or Electronic Lock with Password
- CHAUT - Self Closing Door with stopper at 95°
- HLO – Insulated Hole for External Probe Ø 25mm
- LED - LED Lamp Inside 130cm long, High Brightness
- CS1 - Sliding Aluminum or S/Steel Drawers
- SH1 - Sliding S/Steel Shelves
- SMS - SMS Alarm System
- HC - Humidity Controller
- 3G/WI-FI – On-line connection and remote control system
- RG1 – Graphic Chart Recorder with 52 Paper Disks

