



# Laboratory Refrigerator

| MODEL    | TEMPERATURE RANGE | SET POINT | CAPACITY (LITRES) | EXTERNAL DIMENSIONS (W x D x H cm) | DOOR TYPE   |
|----------|-------------------|-----------|-------------------|------------------------------------|-------------|
| 7000 NFP | 0°C ÷ +20°C       | +4°C      | 820               | 132 x 64 x 203                     | Solid Doors |



**Colour:** Gray, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 90mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 210-240Volt / 50-60Hz  
**Electrical characteristics:** Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 20 Volts)  
**Compressor:** nr.1 Hermetic Type - 600Watt  
**Refrigerant gas:** R452a (R404a and R507a compatible)  
**Door:** : Nr 1 Glass Door  
**Inner setting:** 5 / 7 Shelves/Grids  
**Lighting:** NEON lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 Wheels + 2 adjustable feet

**Visual and acoustic alarm for:**

- High and low temperature
- Open door
- Devices failure
- Probes failures

**OPTIONAL:**

DTLSD3 - Data Logger Touch Screen 5" D3 Velex  
 TC - Twin Compressor  
 SE / ESEDL - Manual or Electronic Lock with Password  
 UPS - Back-up Battery System  
 CHAUT - Self Closing Door  
 HELO - Hole for External Probe  
 LED - LED Lamp Inside  
 CS1 / CS2 - Sliding Movable S/Steel Drawers  
 SH1 / SH2 - Sliding Movable S/Steel Shelves  
 SMS - SMS Alarm System  
 WI-FI/3G-Connection to the Network for remote control online  
 HUC -Humidity Controller

