


## Laboratory Freezer -25 °C



Refrigerator cabinet to preserve pharmaceutical and biological materials.

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
LB 9000NFN	0°C ÷ -25°C	-20°C	560	90 x 64 x 204	Solid Door



### MICRO-PROCESSOR CONTROLLED – DRY CONTACT – UPS 24h

**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, Thic.70mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 210-240Volt / 50-60Hz  
**Electrical characteristics:** Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 20 Volts).  
**Compressor:** No 1 Hermetic Type - 450Watt – ¾ Hp  
**Refrigerant gas:** R452a (R404 and R507a compatible)  
**Door:** : No 1 Solid Door  
**Inner setting:** 5 or 6 Shelves/Grids  
**Lighting:** NEON lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 Wheels + 2 adjustable feet

**Visual and acoustic alarm for:**

- High and low temperature
- Open door
- Devices failure
- Probes failures

### OPTIONAL:

DTLSD3 (1T) – Interactive Data Logger Touch Screen, LCD 5”  
 TC - Twin Compressor (back-up unit)  
 SE / ESEDL - Manual or Electronic Lock  
 CHAUT - Self Closing Door  
 HELO - Hole for External Probe  
 LED - LED Lamp Inside  
 CS2 – Adjustable Sliding Aluminum Drawers  
 SH2 – Adjustable Sliding S/Steel Shelves  
 WI-FI/3G – Online Connection for monitoring and error mess.  
 SMS - SMS Alarm System  
 HC – Humidity controller  
 S – Special Temperature -35°C

