



## Laboratory Medical Refrigerator (LB)

MODEL	TEMPERATURE SET RANGE	SET POINT	CAPACITY (LITRES)	DIMENSIONS (WxDxH cm)	CHAMBERS	DOORS
9018NFP	+10°C ÷ +2°C	+4°C	1180	<b>External</b> 178x64x204 <b>Internal</b> 168x54x130	1 SINGLE	2 GLASS



**DRY CONTACT – UPS (Back-up Battery) – ACCURACY 0.1°C**

**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m<sup>3</sup>, thick. 80mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 210-240Volt / 50-60Hz  
**Compressor:** No. Hermetic Type, 600+600 Watt, ½ Hp + ½ Hp  
**Refrigerant gas:** R452a (compatible with R507a and R404a)  
**Door:** : No. 2 Glass Doors  
**Inner setting:** 5+5 Shelves/Grids  
**Lighting:** NEON lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 6 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

**OPTIONAL:**

DTLSD3(1T)-Interactive Digital Data Logger Touch Screen 5"  
 SE / ESEDL - Manual or Electronic Lock  
 CHAUT - Self Closing Door  
 HELO - Hole for External Probe  
 LED - LED Lamp Inside  
 CS2 - Sliding Aluminum Drawers with transparent front side  
 SH2 - Sliding S/Steel Shelves  
 SMS - SMS Alarm System  
 HC - Humidity Controller  
 3G/WI-FI – On-line connection and remote control system  
 GR – Remote Cooling System  
 TR – Tropical version (for temperature till 48°C and 90% RH)  
 RS485 / ETH – Additional Exit for BMS/PC/LIMS connection

