



Refrigerator cabinet to preserve pharmaceutical and biological materials.

Laboratory Freezer -25 °C

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
9501 NFN	0°C ÷ -25°C	-20°C	1250	164 x 89 x 204	Two Solid Doors



MICRO-PROCESSOR CONTROLLED – UPS (Back-up Battery) DRY CONTACT

- Colour:** Grey, White or any RAL colour
- Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thic.80mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 220-240Volt / 50-60Hz
- Compressor:** No 1 Hermetic Type– 1000 Watts – 1 ¼ HP
- Refrigerant gas:** R452a (R404a and R507a compatible)
- Door:** : No 2 Solid Doors
- Inner setting:** 10/12 Shelves/Grids
- Lighting:** NEON lamp active on opening door
- Electronic controller:** Hi Efficiency display, res. 0,1°C
- Castors and Wheels:** 6 wheels + 2 adjustable feet

- Visual and acoustic alarm for:
- High and low temperature
 - Open door
 - Devices failure
 - Probes failures

OPTIONAL:

- DTLSD3 (1T) - Data Logger Touch Screen 5" Vexel
- TC - Twin Compressor
- SE / ESEDL - Manual or Electronic Lock
- CHAUT - Self Closing Door
- HELO - Hole for External Probe
- LED - LED Lamp Inside
- CS2 - Sliding Movable Aluminum Drawers
- SH2 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI/3G-On-line connection, e-mail warning, real time control
- S – Special Temperature -35°C
- RS385 / ETH – Exit RS485 or Ethernet for remote connection

