



Refrigerator cabinet to preserve pharmaceutical and biological materials.

## Laboratory Freezer -35 °C

MODEL	TEMPERATURE SET RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
9502 NFN(S)	0°C ÷ -35°C	-30°C	1580	164 x 89 x 204	Two Solid Doors



### DRY CONTACT for Remote Alarm Connection

**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 80mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** nr.1 Hermetic Type- 1000 Watts – 1 ¼ HP  
**Refrigerant gas:** R452a (R404a and R507a compatible)  
**Door:** : Nr 2 Solid Doors  
**Inner setting:** 10/12 Shelves/Grids  
**Lighting:** NEON lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 6 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

### OPTIONAL:

DTLS(1T)-Digital Data Logger Touch Screen 5"  
 TC - Twin Compressor  
 SE / ESDL - Manual or Electronic Lock  
 UPS - Back-up Battery System  
 CHAUT - Self Closing Door  
 HELO - Hole for External Probe  
 LED - LED Lamp Inside  
 CS1 / CS2 - Sliding Movable S/Steel Drawers  
 SH1 / SH2 - Sliding Movable S/Steel Shelves  
 SMS - SMS Alarm System  
 HC -Humidity Controller  
 3G/WI-FI – On-line connection and remote control system

