



Laboratory Medical Freezer Ventilated

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
LP460NFP	0°C ÷ -35°C	-30°C	100	45 x 55 x 104	Hinged Solid Door



Back-up Battery System – Dry Contact – Accuracy: 0,1°C

- Colour:** Gray, White or any RAL colour
- Structure:** Internal and external Steel Laminated Plate to assure a Bacteria-Static Activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 70mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 220-240Volt / 50-60Hz
- Compressor:** No.1 Hermetic Type - 350Watt – ¼ Hp
- Refrigerant gas:** R452a (Compatible with R507a and R404a)
- Door:** : No. 1 Solid Door
- Innr setting:** 3 Shelves/Grids OR 2 Drawers (Option)
- Lighting:** NEON lamp active on opening door
- Electronic controller:** Hi Efficiency display, res. 0,1°C
- Castors and Wheels:** 4 adjustable feet

- Visual and acoustic alarm for:**
- High and low temperature
 - Open door
 - Devices failure
 - Probes failures

OPTIONAL:

- DTLS(1T) – Interactive Data Logger with USB – TFT 5"
- SE / ESEDL - Manual or Electronic Lock
- CHAUT - Self Closing Door
- HLO - Hole for External Probe 25mm
- LED - LED Lamp Inside
- CS1 - Sliding Movable S/Steel Drawers
- SH1 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI - Wi-Fi bridge
- HCC - Humidity Controller, humidity setting
- S – Option Special Low Temperature -35°C

