



# Medical Refrigerator 2 Temperature

MODEL	TEMPERATURE RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
4000 CB	+5°C ÷ -25°C / +2°C ÷ +10°C	165+165	67 x 64 x 203	Hinged Solid Doors



**MICRO-PROCESSOR, BACK-UP BATTERY as STANDARD**

- Colour:** Gray, White or any RAL colour
- Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, Thickness 80mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic, condensing water evaporation
- Electric power:** 1 / 210-240Volt / 50-60Hz
- Electrical characteristics:** Shortage Protection with Power Stabilizer
- Compressor:** No 1 Hermetic Type - 0Watt
- Refrigerant gas:** R452a (R404 and R507 compatible)
- Door:** : No 2 Solid Door
- Inner setting:** 1+4 Shelves/Grids ; 2 compartments
- Lighting:** NEON lamp active on opening door
- Elect. controller:** High efficiency display, res. 0,1°C
- Castors and Wheels:** 4 Wheels + 2 adjustable feet

- Visual and acoustic alarm for:
- Hi - Low temperature
  - Open door
  - Devices failure
  - Probes failures

**OPTIONAL:**

- DTLS (2T) – Interactive Data Logger Touch Screen 5"
- SE / ESDL - Manual or Electronic Lock
- CHAUT - Self Closing Door
- HELO - Hole for External Probe
- LED - LED Lamp Inside
- CS1 - Sliding Movable S/Steel Drawers
- SH1 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- S - Special Temperature (freezer), -30°C / -35°C
- WI-FI/3G – On-line Connection, Monitoring and Remote error messages

