



## Combined Medical Refrigerator 2T

MODEL	TEMPERATURE RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
4000CBA	+8°C ÷ +2°C / 0°C ÷ -40°C	110(fre)+220(chi)	67 x 64 x 203	Glass + Solid Door



### DRY CONTACT – ACCURACY 0.1°C – CPU CONTROLLED UPS (Back-up Battery standard)

- Colour:** Grey, White or any RAL colour
- Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
- Insulation:** Polyurethane Foam CFC FREE, 42Kg/m<sup>3</sup>, Thic. 90mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic, condensing water evaporation
- Electric power:** 1 / 210-240Volt / 50-60Hz
- Electrical characteristics:** Shortage Protection with Power Stabilizer
- Compressor:** No 2 Hermetic Type, 400W/600W, ½ HP - ¾ HP
- Refrigerant gas:** R452a (R404 and R507a compatible)
- Door:** : No 2 Glass Doors
- Inner setting:** 1+3 Shelves/Grids ; 2 compartments
- Lighting:** NEON lamp active on opening door
- Elect. controller:** High efficiency display, res. 0,1°C
- Castors and Wheels:** 4 Wheels + 2 adjustable feet

- Visual and acoustic alarm for:
- HI - LOW temperature
  - Open door
  - Devices failure
  - Probes failures

### OPTIONAL:

- DTLSD3 (2T) - Data Logger Touch Screen, LCD 5"
- SE / ESEDL - Manual or Electronic Lock
- CHAUT - Self Closing Door
- HELO - Hole for External Probe
- LED - LED Lamp Inside
- CS1 - Sliding Aluminum Drawers transparent front side
- SH1 - Sliding Adjustable S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI/3G- On-line Monitoring and Error messages e-mail

