

no frost system
Refrigerator cabinet to preserve pharmaceutical and biological materials.

Medical Refrigerator 2 Temperature

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
4102 CB	+0°C ÷ -25°C / +2°C ÷ +10°C	+4°C / -20°C	170+170	67 x 64 x 20	Solid or Glass



Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 90mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic, condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Shortage Protection with Power Stabilizer
Compressor: nr.1 Hermetic Type - 600Watt
Refrigerant gas: R452a (R404 and R507a compatible)
Door: : Nr 2 Glass or Solid Doors
Inner setting: 1+4 or 3+3 Shelves/Grids ; 2 compartments
Lighting: NEON lamp active on opening door
Elect. controller: High efficiency display, res.0,1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- Hi - Low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

- DTLS (2T) - Data Logger Touch Screen Velex D3 5"
- GR2 - Graphic Chart Recorder with paper disks
- SE / ESDL - Manual or Electronic Lock
- UPS - Back-up Battery System
- HELO - Hole for External Probe
- LED - LED Lamp Inside
- CS1 / CS2 - Sliding Movable S/Steel Drawers
- SH1 / SH2 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- S - Special Temperature (freezer), -30°C / -35°C
- WI-FI/3G - Remote connection, on-line monitoring

LABORATORY					
SET	TEKNALAB				SET
4.0°					-25.0°
4.2°		-24.5°			
LOW	HIGH	16:03	LOW	HIGH	
1.0°	11.0°	15/08/2015	-40.0°	-10.0°	
KEY A	LIGHT A		KEY B	LIGHT B	

