



## Combined Unit 2 Temp., 2 Compartments

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOORS
MT8000CB	+10/+2°C ÷ 0/-25°C	+4°C/-20°C	400+400	132 x 64 x 204	Solid Doors



**MICRO-PROCESSOR CONTROLLED – BACKUP BATTERY DRY CONTACT (NA – NC) for Remote Alarm Connection**

**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY™ to assure a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 43Kg/m3, thic.60mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** No. 2 Hermetic Type – 400+400 Watts – ½ HP each  
**Refrigerant gas:** R452a (R404a and R507a compatible)  
**Door:** No 2 Solid Doors (**GLASS on request**)  
**Inner setting:** 5+5/8+8 Shelves/Grids/Drawers  
**Lighting:** LED light active on opening door, 6000K, 130cm long  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 6 wheels + 2 adjustable feet

Main Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

**MAIN ACCESSORIES & OPTIONS:**

DTLSD3 (2T) - Data Logger TFT 5", LCD, RGB with USB  
 TC - Twin Compressor  
 SE / ESEDL - Manual or Electronic Lock with password  
 CHAUT - Self Closing Door with stopper at 95°  
 HLO - Hole for External Probe 25mm  
 CS2 - Sliding Movable Aluminum Drawers  
 SH2 - Sliding Movable S/Steel Shelves  
 SMS - SMS Alarm System  
 WI-FI/3G-On-line connection, e-mail warning, real time control  
 S – Special Temperature -35°C  
 RS485 / ETH – Exit RS485 or Ethernet for remote connection  
 RG2 – Graphic Chart Recorder 2 temperatures with 52 charts

**OPTIONS:  
SLIDING DRAWERS**



**INTERACTIVE DATA LOGGER 2 TEMPERATURES**

