



Medical Refrigerator/Freezer 2 Temp.

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
MT9120CB	0°C ÷ -25°C / +2°C ÷ +10°C	-20°C / +4°C	250+250	90 x 64 x 204	Glass Doors



DRY CONTACT for BMS – BACK-UP BATTERY 24/36hrs
Colour: Grey, White or any RAL colour
Structure: Internal and external Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY® to assure a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 70mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic, condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Shortage Protection with Power Stabilizer
Compressor: No.2 Hermetic Type – ½ + ½ HP - 400Watt x2
Refrigerant gas: R452a (R404a and R507a compatible)
Door: No 2 Glass Doors, Double and Triple Glass
Inner setting: 5+5 Shelves/Grids ; 2 compartments
Lighting: NEON lamp active on opening door
Elect. controller: High efficiency display, Accuracy 0,1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Main Visual and acoustic alarm for:

- HI – LOW Temperature
- Open door
- Mains failure
- Probes failures

MAIN OPTIONS:

- DTLSD3(2T) –Interactive Data Logger TFT 5", RGB Colors
- SE / ESEDL - Manual or Electronic Lock with Password
- CHAUT - Self Closing Door with stopper at 95°
- HLO – Insulated Hole for External Probe Ø25mm
- LED -LED Light Inside, 130cm long, High Brightness 6000k
- CS1 - Sliding Aluminum OR S/S Drawers, edge 100mm H
- SH1 - Sliding INOX S/Steel Shelves
- SMS - SMS Alarm System
- S - Special Temperature (freezer), -35°C
- WI-FI/3G – On-line Connection, Remote Monitoring and Automatic error messages sending, Weekly report
- R290 - Option GAS R290

