


Pharmacy Medical Freezer



MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
0041 NFN	0°C ÷ -25°C	-20°C	210	67 x 64 x 140	Triple Glass Door



ACCURACY 0.1°C - DRY CONTACT – BACK-UP BATTERY 36hrs

- Colour:** Gray, White or any RAL colour
- Structure:** Internal and external Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY™ to assure a Bacteria-Static Act.
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 60mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 210-240Volt / 50-60Hz
- Electrical characteristics:** Shortage Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 30 Volts) only with Option DTLSD3
- Compressor:** No.1 Hermetic Type - 450Watt ; ½ Hp
- Refrigerant gas:** R452a (R404 and R507a compatible); CFC FREE
- Door:** No. 1 Glass Door
- Inner setting:** 3 / 4 Shelves/Grids/Drawers
- Lighting:** NEON lamp active on opening door
- Electronic controller:** Medical Grade, Accuracy. 0,1°C
- Castors and Wheels:** 4 Wheels + 2 adjustable feet

- Main Visual and acoustic alarms for:
- HI and LOW temperature
 - Open door
 - Devices failure
 - Probes failures

MAIN OPTIONS:

- DTLSD3 – Interactive Data Logger TFT 5" LCD, RGB Colors
- SE / ESEDL - Manual or Electronic Lock with Password
- CHAUT - Self Closing Door with stopper at 95°
- HLO - Hole for External Probe Ø 25mm
- LED - LED Lamp Inside 80cm long, High Brightness
- CS1 –Sliding Aluminum or S/S Drawers transparent front side
- SH1 - Sliding S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI/3G–Connection to the Network for remote control online
- HUC -Humidity Controller
- RG1 – Graphic Chart Recorder with 52 weekly paper disks

