

Pharmacy Medical Refrigerator

no frost system
Refrigerator cabinet to preserve pharmaceutical and biological materials.

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
0051 NFP	+2°C ÷ +10°C	+4°C	240	76 x 64 x 140	Hinged Glass Door



ACCURACY: 0.1°C
DRY CONTACT for Remote Alarm Connection
BACK-UP Battery 12V/DC for Display & Controller (24Hrs)

Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 70mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Shortage Protection, Power Stabilizer Linear Regulation of Voltage In (+/-35 Volts)
Compressor: No.1 Hermetic Type – 1/3 Hp 450Watt
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : No 1 Glass Door
Inner setting: 3 to 4 Shelves/Grids/Drawers
Lighting: NEON lamp active on opening door (or LED Light)
Electronic controller: Hi Efficiency Electronic Controller, LCD display
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

- DTLSD3 – Interactive Data Logger Touch Screen 5" LCD
- SE / EESDL - Manual or Electronic Lock with Password
- CHAUT - Self Closing Door with stopper at 95°
- HLO – Insulated hole Ø 25mm for External Probe
- LED - LED Lamp Inside 90cm High Brightness
- CS1– Sliding Drawers on bearings with Transparent Front Side
- SH1 - Sliding S/Steel Shelves on bearings
- SMS - SMS Alarm System
- WI-FI/3G–Connection to the Network for remote control online
- TC- Tropical Cooling System (for Temp. over 32°C, RH 98%)
- HUC - Humidity Controller

