



Pharmacy Refrigerator 2 Compartments

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
10000 NFP	+2÷+10°C/+2÷+10°C	+4/+4°C	470+470	150 x 64 x 204	2 Glass Doors



BACK-UP BATTERY and DRY CONTACT STANDARD

Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 80mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 20 Volts)
Compressor: No. 2 Hermetic Type – 500+500Watt – ½ Hp each
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : No 2 Glass Doors
Inner setting: 5 +5 Shelves/Grids
Light: Lights active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 6 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and ILOWtemperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLSD3(2T) – Interactive Data Logger Touch Screen 5”
 SE / ESEDL - Manual or Electronic Lock with Password
 RG2 – Graphic Chart Recorder 2 Temp. with Paper Disks
 CHAUT - Self Closing Door
 HELO - Hole for External Probe
 LED - LED Lamp Inside
 CS2 - Sliding Movable S/Steel Drawers
 SH2 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm System
 WI-FI/3G–Connection to the Network for remote control online
 HC -Humidity Controller

