



Pharmacy Refrigerator 2 Compartments

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
10010 NFP	+2÷+10°C/+2÷+10°C	+4/+4°C	590+590	132 x 89 x 204	2 Glass Doors



BACK-UP BATTERY and DRY CONTACT STANDARD

- Colour:** Gray, White or any RAL colour
- Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 70mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 210-240Volt / 50-60Hz
- Electrical characteristics:** Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 20 Volts)
- Compressor:** No. 2 Hermetic Type – 600+600Watt – ½ Hp each
- Refrigerant gas:** R452A (R507a and R404a compatible)
- Door:** : No 2 Glass Doors
- Inner setting:** 5 +5 Shelves/Grids/Drawers (max 8+8)
- Light:** Lights active on opening door
- Electronic controller:** Hi Efficiency display, res. 0,1°C
- Castors and Wheels:** 6 Wheels + 2 adjustable feet

- Visual and acoustic alarm for:
- HI and LOW temperature
 - Open door
 - Devices failure
 - Probes failures

OPTIONAL:

- DTLSD3-2T – Interactive Data Logger Touch Screen 5" + USB
- SE / ESEDL-2D - Manual or Electronic Lock with Password
- RG2 – Graphic Chart Recorder 2 Temp. with Paper Disks
- CHAUT - Self Closing Door
- HLO - Hole for External Probe
- LED - LED Lamp Inside
- CS2 - Sliding Movable S/Steel Drawers
- SH2 - Sliding Movable S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI/3G–Connection to the Network for remote control online
- HC -Humidity Controller

