


# Pharmacy - Medical Refrigerator 3 Doors



MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
PM1510NFP	+1°C ÷ +10°C	+4°C	1312	164 x 89 x 204	3 Glass Doors



**DRY CONTACT – BACK-UP Battery 24hrs –Accuracy 0.1°C**  
**Colour:** Gray, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 80mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** No. 1 Hermetic Type– 1000 Watts – 1 ¼ HP  
**Refrigerant gas:** R452a (R404a and R507a Compatibles)  
**Door:** : No 3 Glass Doors  
**Inner setting:** 5+5+5 Shelves/Grids  
**Lighting:** No. 3 NEON (or LED) lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 6 wheels + 3 adjustable feet

Visual and acoustic alarm for: - HI – LOW Temperature  
 - Open door  
 - Devices failure  
 - Probes failures

**OPTIONAL:**  
 DTLS(1T)- Interactive Digital Data Logger Touch Screen 5"  
 TC - Twin Compressor  
 SE / ESDL - Manual or Electronic Lock with Password  
 CHAUT - Self Closing Door  
 HLO - Hole for External Probe  
 LED - LED Lamp Inside  
 CS1 - Sliding Movable S/Steel-Aluminum Drawers  
 SH1 - Sliding Movable S/Steel Shelves  
 SMS - SMS Alarm System  
 HC - Humidity Controller  
 3G/WI-FI – On-line connection and remote control system  
 GR – Remote Cooling System

