

# Vaccine Pharma Refrigerator - 3 Compartments , 3 Cooling Systems

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
PM 2010 NFP	+2°C ÷ +10°C	+4°C	560lts x3	266 x 64 x 204	Three Glass Doors



**Alarm: HI Limit +8°C ; LOW Limit +2°C**  
**UPS (Back-up battery 24hr)**  
**Dry Contact for Remote Alarm Connection**

**Colour:** Gray, White or any RAL colour  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 90mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 210-240Volt / 50-60Hz  
**Compressor:** No 3 Hermetic Type – 600Watt x3 – ½ HP x 3  
**Refrigerant gas:** R507A  
**Door:** : No. 3 Glass Door  
**Inner setting:** 7+7+7 Drawers Max ; 6+6+6 Grids /Shelves  
**Lighting:** NEON lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 6 Wheels + 3 adjustable feet

Visual and acoustic alarm for:

- High and Low Temperature
- Open door
- Devices failure
- Probes failures

**OPTIONAL:**

DTLSD3 – Interactive Data Logger Touch Screen 5”  
SE / ESDL - Manual or Electronic Lock with Password  
UPS - Back-up Battery System  
CHAUT - Self Closing Door  
HELO - Hole for External Probe  
LED - LED Lamp Inside  
CS1 - Sliding Movable S/Steel Drawers  
SH1 - Sliding Movable S/Steel Shelves  
WI-FI/3G – On-line Monitoring and Remote Alarm System  
SMS – Alarms and Warnings Message System  
HC – Humidity Controller

