


Pharmacy - Medical Freezer



MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
PM 2100 NFN	+5°C ÷ -25°C	-20°C	250	46 x 64 x 204	Triple Glass Door




Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 90mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 20 Volts)
Compressor: nr.1 Hermetic Type - 400Watt
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : Nr 1 Triple Glass Door
Inner setting: 5 / 7 Shelves/Grids
Lighting: NEON lamp active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLS(1T) - Data Logger Touch Screen 5" D3 Vexel
 TC - Twin Compressor
 SE / ESDL - Manual or Electronic Lock with Password
 UPS - Back-up Battery System
 CHAUT - Self Closing Door
 HELO - Hole for External Probe
 LED - LED Lamp Inside
 CS1 / CS2 - Sliding Movable S/Steel Drawers
 SH1 / SH2 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm System
 WI-FI/3G-Connection to the Network for remote control online
 HLIC -Humidity Controller

LABORATORY				
OUTPUTS			16:00 15/08/2015	
<h1>-20.1°</h1>				
LOW	HIGH	SET	EVAPORATOR	CONDENSER
- 22.0°	-13.0°	-20.0°	-35.4°	32.1°
KEY		LIGHT		

