

Pharmacy & Medical Freezer

MODEL	TEMP. RANGE		SET POINT	CAPACITY (LITRES)	DIMENSIONS (WxDxH cm)		DOOR TYPE
	MAX	MIN.			External	Internal	
4100NFN	0°C	-25°C	-20°C(adj.)	400	67 x 64 x 204	57 x 54 x 130	Triple Glass Door



DRY CONTACT-UPS(Back-up 24hrs)-MICRO PROCESSOR


Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, Th. 90mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage fluctuations
Compressor: No 1 Hermetic Type - 500Watt – ½ HP
Refrigerant gas: R452A (R404A and R507a compatible)
Door: : No 1 Triple Glass Door
Inner setting: 5 / 6 Shelves/Grids
Lighting: NEON lamp active on opening door
Electronic controller: Hi Efficiency display, Accuracy: 0,1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLSD3 – Interactive Data Logger Touch Screen 5”
 TC - Twin Compressor
 SE / ESEDL - Manual or Electronic Lock with Password
 CHAUT - Self Closing Door
 HELO - Hole for External Probe
 LED - LED Lamp Inside
 CS1 - Sliding Movable S/Steel Drawers
 SH1 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm Automatic SMS Sending System
 WI-FI/3G-Online Conn. Real Time Control and Error Messages
 RS485 / ETHERNET – Additional exit for BMS Connection
 RG – Graphic Chart Recorder
 PRBG – Shielded Probe PT100 for temperature stability

LABORATORY				
OUTPUTS			16:00 15/08/2015	
<h1>-20.1°</h1>				
LOW	HIGH	SET	EVAPORATOR	CONDENSER
- 22.0°	-13.0°	-20.0°	-35.4°	32.1°
KEY			LIGHT	

