


Pharmacy - Medical Freezer



Refrigerator cabinet to preserve pharmaceutical and biological materials.

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
PM 5020 NFN	0°C ÷ -25°C	-20°C	750	83 x 89 x 204	Triple Glass Door



DRY CONTACT – MICRO PROC. CONTROLLED – UPS 24hrs

Colour: Gray, White or any RAL colour

Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity

Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 80mm

Refrigeration type: Ventilated (NO-FROST)

Defrosting: Automatic with condensing water evaporation

Electric power: 1 / 210-240Volt / 50-60Hz

Electrical characteristics: Short-Circuit Protection, Power Stabilizer with Linear Regulation of Voltage for not constant voltage(+/- 20 Volts)

Compressor: No. 1 Hermetic Type – ¾ HP - 600Watt

Refrigerant gas: R507A (R404 compatible)

Door: : No 1 Triple Glass Door

Inner setting: 5 to 7 Shelves/Grids

Lighting: NEON lamp active on opening door (LED Light as Option)

Electronic controller: Hi Efficiency display, res. 0,1°C

Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLSD3(1T) – Interactive Data Logger Touch Screen 5"

TC - Twin Compressor with back-up unit and auto switch-over

SE / ESEDL - Manual or Electronic Lock with Password

CHAUT - Self Closing Door with stopper at 90°

HLO – Pass-thru insulated hole 25mm for External Probe

LED - LED Lamp Inside

CS2 - Sliding Movable S/Steel or Aluminum Drawers

SH2 - Sliding Movable S/Steel Shelves

SMS - SMS Alarm System

WI-FI/3G–Connection to the Network for remote control online

HC -Humidity Controller

AB – S/steel AISI 304 Inside and/or Outside

S – Option special temperature -35°C on request

TR – Tropicalized version

