



Pharmacy - Medical Freezer

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
7100NFN Slim	0°C ÷ -25°C	-20°C	715	132 x 55 x 204	Two Glass Doors



DRY CONTACT – BACK-UP BATTERY - ACCURACY 0.1°C
Colour: Grey, White or any RAL colour
Structure: Internal and external S/S Laminated Plate with FINGER-PRINT PROOF TECHNOLOGY™ to ASSURE a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m³, thick. 70mm
Refrigeration type: Ventilated – Forced Air Circ. (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 220-240Volt / 50-60Hz
Compressor: No. 1 Hermetic Type– 1100 Watts – 1 ½ HP
Refrigerant gas: R452a (compatible with R404a and R507a)
Door: No 2 Glass Doors
Inner setting: 10 to 16 Shelves/Grids, Max Load of 45Kg each
Light: NEON/LED tube active when door open or when necessary
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 4 wheels + 2 adjustable feet

Main Visual and acoustic alarm:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

MAIN OPTIONS:

DTLSD3(1T)- Interactive Data Logger TFT 5", RGB Colour
 TC - Twin Compressor
 SE / ESEDL - Manual or Electronic Lock with Password
 CHAUT - Self Closing Door
 HLO – Insulated Hole for External Probe Ø 25mm
 LED – 2 LED Tube 130cm long , High Brightness
 CS1 - Sliding Aluminum or S/S Drawers Transparent Front
 SH1 - Sliding Plane S/S Shelves
 SMS - SMS Alarm System with self-messages sending
 LW – Swivel Lockable Wheels
 3G/WI-FI – Wireless on-line connection and remote control system for real time monitoring and online unit set-up
 GR – Remote Cooling System



Nr 5 + 5 665 x 680 mm

