



## Pharma - Medical Refrigerator

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
PM 7100NFP	+2°C ÷ +10°C	+4°C(Adj.)	820 NET	132 x 64 x 204	Two Glass Doors



**DRY CONTACT – BACK-UP BATTERY - ACCURACY 0.1°C**  
**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external S/S Laminated Plate with FINGER-PRINT PROOF TECHNOLOGY™ to assure a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m<sup>3</sup>, thick. 60mm  
**Refrigeration type:** Ventilated – Forced Air Circ. (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** No. 1 Hermetic Type– 800 Watts – 1 ¼ HP  
**Refrigerant gas:** R452a (compatible with R404a and R507a)  
**Door:** No 2 Glass Doors  
**Inner setting:** 10 to 16 Shelves/Grids, Max Load of 45Kg each  
**Light:** NEON/LED tube active when door open or when necessary  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 wheels + 2 adjustable feet

Main Visual and acoustic alarm:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

### MAIN OPTIONS:

DTLSD3(1T)- Interactive Data Logger TFT 5", RGB Colour  
 TC - Twin Compressor  
 SE / ESEDL - Manual or Electronic Lock with Password  
 CHAUT - Self Closing Door  
 HLO – Insulated Hole for External Probe Ø 25mm  
 LED – 2 LED Tube 130cm long , High Brightness  
 CS1 - Sliding Aluminum or S/S Drawers Transparent Front  
 SH1 - Sliding Plane S/S Shelves  
 SMS - SMS Alarm System with self-messages sending  
 LW – Swivel Lockable Wheels  
 3G/WI-FI – Wireless on-line connection and remote control system for real time monitoring and online unit set-up  
 GR – Remote Cooling System

### OPTION INTERACTIVE DIGITAL DATA LOGGER TFT 5" , RGB COLOURS

