



Pharmacy Medical Refrigerator 2 Zones

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOORS
PM 9018NFP	+10°C ÷ +2°C	+4°C	1180	178 x 64 x 250	2 Glass Doors



DRY CONTACT – BACK-UP BATTERY - ACCURACY 0.1°C
Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Laminated Plate with FINGER-PRINT PROOF TECHNOLOGY™ to assure Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 70mm
Refrigeration type: Ventilated – Forced Air Circ. (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 220-240Volt / 50-60Hz
Compressor: no.2 Hermetic Type – 1200 Watt , 1 ¼ HP
Refrigerant gas: R452a
Door: No. 2 Glass Doors
Inner setting: 5+5 Shelves/Grids
Lighting: LED lamp active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 6 wheels + 2 adjustable feet

Main Visual and acoustic alarm:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures

MAIN OPTIONS:

- DTLSD3 (1T)- Interactive Data Logger TFT 5", RGB Color
- TC - Twin Compressor
- SE / ESEDL - Manual or Electronic Lock with Password
- CHAUT - Self Closing Door with stopper at 95°
- HLO – Insulated Hole for External Probe Ø 25mm
- CS2 - Sliding Aluminum or S/S Drawers Transparent Front
- SH2 - Sliding Perforated S/S Shelves
- SMS - SMS Alarm System with self-messages sending
- LW – Swivel Lockable Wheels
- 3G/WI-FI – Wireless on-line connection and remote control system for real time monitoring and online unit set-up
- GR – Remote Cooling System
- RG1 - Graphic Chart Recorder with 52 weekly paper charts

