

no frost system
Refrigerator cabinet to preserve pharmaceutical and biological materials.

PHARMACY MEDICAL REFRIGERATOR

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
9120-2D NFP	+10°C ÷ +2°C	+4°C (adj)	560	90 x 64 x 204	2 Glass Doors



ACCURACY: 0.1°C - BACK-UP BATTERY - DRY CONTACT
Colour: Gray, White or any RAL colour
Structure: Internal and external S/S or Steel Laminated Plate, FINGER PRINT PROOF TECHNOLOGY™ to assure a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m³, thick.60mm
Refrigeration type: Ventilated (NO-FROST), FORCED AIR CIRC.
Defrosting: Automatic with condensing water evaporation, Hot Gas
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Shortage Protection and Power Stabilizer with Linear Regulation of Voltage (+/- 20 Volts)
Compressor: No.1 Hermetic Type – 600Watt – ½ Hp
Refrigerant gas: R452a (R507a and R404a compatible)
Door: : No. 2 Glass Door
Inner setting: 5+5 to 7+7 Shelves/Grids/Drawers
Light: Lights active on opening door (LED Tube or Fluorescent)
Electronic controller: Hi Efficiency display
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLSD3 – Interactive Data Logger TFT 5” with USB and SD
 SE / ESEDL - Manual or Electronic Lock with Password
 CHAUT - Self Closing Door with stopper at 95°
 HLO - Hole for External Probe Ø 25mm
 LED - LED Lamp Inside High Brightness
 CS1 - Sliding Aluminum or S/S Drawers on telescopic rails
 SH1 - Sliding S/S Drawers on telescopic rails
 SMS - SMS Alarm System
 WI-FI – Bridge for Cloud Connection and real time monitoring
 3G – Online Connection for remote control through SIM Card
 TC – Twin Cooling System with Auto-Switchover when faulty

(OPTION) INTERACTIVE DIGITAL DATA LOGGER TFT 5” USB/SD

