

no frost system
 Refrigerator cabinet to preserve pharmaceutical and biological materials.

Combined Refrigerator 2 Positive Temp.

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	EXT. DIMENSIONS (W x D x H cm)	DOOR TYPE
9120NFP	+2°C ÷ +10°C / +2°C ÷ +10°C	+4°C / +4°C	250+250	90 x 64 x 204	2 Glass Doors



DRY CONTACT – BACK-UP Battery 24hrs – Accuracy: 0.1°C
Colour: Grey, White or any RAL colour
Structure: Internal and external Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thick.60mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic, condensing water evaporation
Electric power: 1 / 210-240Volt / 50-60Hz
Electrical characteristics: Shortage Protection with Power Stabilizer
Compressor: No.2 Hermetic Type – ½ + ½ HP - 400Watt x2
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : No 2 Glass Doors
Inner setting: 5+5 Shelves/Grids; 2 Independent Compartments
Lighting: NEON lamp active on opening door
Elect. controller: High efficiency display, res.0.1°C
Castors and Wheels: 4 Wheels + 2 adjustable feet

Visual and acoustic alarm for:

- Hi - Low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

- DTLSD3 (2T) – Interactive Data Logger Touch Screen 5"
- SE / ESEDL - Manual or Electronic Lock with Password
- CHAUT - Self Closing Door with stopper at 95°
- HLO - Hole for External Probe Ø 25mm
- LED - LED Lamp Inside
- CS1 - Sliding Aluminum or S/Steel Drawers
- SH1 - Sliding S/Steel Shelves
- SMS - SMS Alarm System
- WI-FI/3G – On-line Connection, Monitoring and Remote error messages
- TR – Tropical Version
- RG2 – Graphic Chart Recorder 2 Temperature
- RS485 – Serial Port for BMS/PC Connection

