



## Pharmacy Refrigerator Sliding Doors

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	DIMENSIONS	DOOR TYPE
7100XL-s NFP	+2°C ÷ +10°C	+4°C	1'040	Ext. 164W x 89D x 204H cm Int. 154W x 79D x 130H cm	Sliding Doors



### BACK-UP BATTERY 12V,2Amp – DRY CONTACT(NC-NO)

**Colour:** Grey, White or any RAL colour  
**Structure:** Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY™ to assure a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 60mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** No.1 Hermetic Type – 1000 Watt – 1 ¼ HP  
**Refrigerant gas:** R452a (Compatible with R507a and R404a)  
**Door:** No 2 Sliding Glass Doors  
**Inner setting:** from 10 to 16 Shelves or Grids  
**Lighting:** LED lamp active on opening door, 130cm long, 6000K  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures
- Compressor failure

### MAIN OPTIONS:

DTLSD3(1T) – Interactive Data Logger TFT 5" with USB  
 TC - Twin Compressor  
 SE / ESEDL - Key or Electronic Lock with Password (DTLD3)  
 HLO - Hole for External Probe Ø25mm  
 PIS – Adjustable S/S AISI 304 Scotch Brite shelves  
 3G/SMS - SMS Alarm System  
 WI-FI – Remote connection and alarm sending  
 RG1 – Graphic Chart Recorder with 52 Paper Disks + Pen

### DTLSD3 TFT 5" RGB Colors (OPTION)

