



## Pharmacy Refrigerator Sliding Doors

MODEL	TEMPERATURE RANGE	SET POINT	CAPACITY (LITRES)	DIMENSIONS	DOOR TYPE
PM 9501-sNFP	+2°C ÷ +10°C	+4°C	1'250	Ext. 132W x 89D x 204H cm Int. 122W x 79D x 130H cm	Sliding Doors



**ACCURACY: 0.1°C – DRY CONTACT – BACK-UP BATTERY**

**NATURAL GAS R290 AVAILABLE ON REQUEST**

**Colour:** Grey, White or any RAL colour  
**Structure:** Internal and external Steel Laminated Plate with FINGER PRINT PROOF TECHNOLOGY to assure a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thick. 60mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz  
**Compressor:** No 1 Hermetic Type – 400 W – ½ Hp  
**Refrigerant gas:** R452a (Compatible to R404a and R507a)  
**Door:** No 2 Sliding Glass Doors  
**Inner setting:** from 5+5 to 8+8 Shelves or Grids  
**Lighting:** LED lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 wheels + 2 adjustable feet  
**Noise:** 52 dB

**Main Visual and acoustic alarm for:**

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures
- Compressor failure

**MAIN OPTIONS:**

RG1 – Graphic Chart Recorder with weekly paper disks  
 FLXP – Data logger with WI-FI connection and Direct WI-FI  
 DTLSD3 – Interactive Data Logger TFT5” RGB Colors, USB  
 TC - Twin Compressor  
 SE / ESEDL - Manual or Electronic Lock with Password  
 HLO - Hole for External Probe  
 WI-FI / 3G – Online Monitoring and Alarm Sending  
 SMS - SMS Alarm System

**INTERACTIVE DATA LOGGER TFT5” (DTLSD3) - OPTION AVAILABLE ON REQUEST**

