


Pharma-Lab Refrigerator(Pass-Through)



MODEL	TEMPERATURE RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
10010 PT	+2°C ÷ +10°C	590+590	132 x 89 x 204	4 Hinged Glass Doors



Colour: Gray, White or any RAL colour
Structure: Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity
Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 80mm
Refrigeration type: Ventilated (NO-FROST)
Defrosting: Automatic with condensing water evaporation
Electric power: 1 / 220-240Volt / 50-60Hz
Compressor: nr.2 Hermetic Type – 600+600Watt , ½ Hp each
Refrigerant gas: R452a (R404a and R507a compatible)
Door: : Nr 2 Glass Doors
Inner setting: 5+5 Shelves/Grids
Lighting: NEON lamp active on opening door
Electronic controller: Hi Efficiency display, res. 0,1°C
Castors and Wheels: 6 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- High and low temperature
- Open door
- Devices failure
- Probes failures

OPTIONAL:

DTLS(1T)-Digital Data Logger Touch Screen 5"
 TC - Twin Compressor
 SE / ESDL - Manual or Electronic Lock
 UPS - Back-up Battery System
 CHAUT - Self Closing Door
 HELO - Hole for External Probe
 LED - LED Lamp Inside
 CS1 / CS2 - Sliding Movable S/Steel Drawers
 SH1 / SH2 - Sliding Movable S/Steel Shelves
 SMS - SMS Alarm System
 HUC -Humidity Controller
 3G/WI-FI – On-line connection and remote control system

