


## Pass-Through Refrigerator for Lab



MODEL	TEMPERATURE RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
4100 PT	+10°C ÷ +2°C	400	67 x 64 x 204	2 Glass Doors



**Color:** Gray, White or any RAL color  
**Structure:** Internal and external S/S Steel Laminated Plate to guarantee a Bacteria-Static Activity  
**Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m3, thickness 90mm  
**Refrigeration type:** Ventilated (NO-FROST)  
**Defrosting:** Automatic with condensing water evaporation  
**Electric power:** 1 / 220-240Volt / 50-60Hz, 13 Amp  
**Compressor:** nr.1 Hermetic Type - 400Watt  
**Refrigerant gas:** R452a (R404a and R507a compatible)  
**Door:** : Nr 2 Glass Door (Pass-through)  
**Inner setting:** 5 Shelves/Grids  
**Lighting:** NEON lamp active on opening door  
**Electronic controller:** Hi Efficiency display, res. 0,1°C  
**Castors and Wheels:** 4 Wheels + 2 adjustable feet

**Visual and acoustic alarm for:**

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures
- Power failures

### OPTIONAL:

- DTLS (1T) - Digital Data Logger
- TC - Twin Compressor
- SE / ESEDL - Manual or Electronic Lock
- UPS - Back-up Battery System
- CHAUT - Self Closing Door
- HELO - Hole for External Probe
- LED - LED Lamp Inside
- CS2 - Sliding Movable S/Steel Drawers
- SH2 - Sliding Movable S/Steel Shelves
- HUC -Humidity Controller
- SMS/3G/WI-FI – Remote connection

