



Pass-Through Refrigerator for Lab

MODEL	TEMPERATURE RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
5030 PT	10°C ÷ +2°C	880	95 x 89 x 204	Front and Rear Doors



DRY CONTACT – BACK-UP BATTERY (ups) – ACCURACY 0.1°

Colour: Grey, White or any RAL colour

Structure: Internal and External Steel Laminated Plate to assure a Bacteria-Static Activity

Insulation: Polyurethane Foam, CFC FREE, 42Kg/m3, Thick. 70mm

Refrigeration type: Ventilated (NO-FROST)

Defrosting: Automatic with condensing water evaporation

Electric power: 1 / 220-240Volt / 50-60Hz

Compressor: No 1 Hermetic Type – ¾ Hp – 700 Watts

Refrigerant gas: R452a (R404a and R507a compatible)

Door: No. 2 Solid or Glass Hinged Doors with alternate opening

Inner setting: 5/6 Adjustable Shelves or Grids

Lighting: Neon or LED (optional) lights

Electronic controller: Hi Efficiency display, res. 0,1°C

Castors and Wheels: 4 wheels + 2 adjustable feet

Visual and acoustic alarm for:

- HI and LOW temperature
- Open door
- Devices failure
- Probes failures
- Compressor failure
- Condenser failure
- UPS failure

OPTIONAL:

DTLSD3 – Interactive Data Logger Touch Screen Vexx 5"

SE / ESDL - Manual or Electronic Lock alternate opening

CHAUT - Self Closing Door with stopper at 90°

LED – Led light when door open

HELO - Hole for External Probe

CS2 - Sliding Movable Aluminum Drawers

SH2 - Sliding Movable S/Steel AISI 304 Shelves

PIS – Perforated S/Steel AISI 304 Shelves

SMS - SMS Alarm System

3G/WI-FI – Online connection for remote monitoring system

GR – Remote cooling System

