


Pass-Through for Lab & Pharmacy



MODEL	TEMPERATURE RANGE	CAPACITY (LITRES)	EXTERNAL DIMENSIONS (W x D x H cm)	DOOR TYPE
PT9502PT	10°C ÷ +2°C	1'560	164 x 89 x 204	Alternate Opening S-Closing Glass Doors



DRY CONTACT- BACK-UP BATTERY 12Vdc – ACCURACY 0.1°

- Colour:** Grey, White or any RAL colour
- Structure:** Internal and External Steel Laminated Plate with Finger Print Proof Technology® to assure a Bacteria Static activity
- Insulation:** Polyurethane Foam, CFC FREE, 42Kg/m³, Thick.60mm
- Refrigeration type:** Ventilated (NO-FROST)
- Defrosting:** Automatic with condensing water evaporation
- Electric power:** 1 / 220-240Volt / 50-60Hz
- Compressor:** No 1 Hermetic Type – 1 ¼ Hp – 1000 Watts
- Refrigerant gas:** R452a (R404a and R507a compatible)
- Door:** No. 4 Glass Hinged Doors with alternate opening
- Inner setting:** 5/6 Adjustable Shelves or Grids
- Lighting:** Neon or LED (optional) lights
- Electronic controller:** Hi Efficiency display, res. 0,1°C
- Castors and Wheels:** 6 wheels + 6 adjustable feet
- Visual and acoustic alarm for:**
 - HI and LOW temperature
 - Open door
 - Devices failure
 - Probes failures
 - Compressor failure
 - Condenser failure
 - UPS failure

OPTIONAL:

- DTLSD3 – Interactive Data Logger TFT 5", LCD, USB
- SE / ESDL - Manual or Electronic Lock alternate opening
- CHAUT - Self Closing Door with stopper at 95°
- LED – Led light when door open
- HELO - Hole for External Probe
- CS2 - Sliding Movable Aluminum Drawers
- SH2 - Sliding Movable S/Steel AISI 304 Shelves
- PIS – Perforated S/Steel AISI 304 Shelves
- SMS - SMS Alarm System
- 3G/WI-FI – Online connection for remote monitoring system
- GR – Remote cooling System

